

The newverbs Package

Martin Scharrer
martin@scharrer-online.de

CTAN: <http://www.ctan.org/pkg/newverbs>

Version v1.4 – 2019/09/09

Abstract

This package allows the definition of `\verb` variants which add TeX code before and after the verbatim text. When used together with the `shortvrb` package it allows the definition of short verbatim characters which use this variants instead of the normal `\verb`.

1 Usage

1.1 Defining new variants of `\verb`

```
\newverbcommand{<\macro>}{<code before>}{<code after>}  
\renewverbcommand{<\macro>}{<code before>}{<code after>}  
\provideverbcommand{<\macro>}{<code before>}{<code after>}
```

This macros allow the definition of `\verb` variants. The verbatim content is processed using `\verb`, but the variants can add TeX code before and after it. The three definition macros use `\newcommand*`, `\renewcommand*` and `\providecommand*` internally to define `<macro>`, respectively. Afterwards `<macro>` can be used like `\verb`. The star version of `<macro>` will use `\verb*`.

See the implementation of `\qverb` in section 3.2 for an example.

1.2 Provided `\verb` variants

Two `\verb` variants are provided (i.e. with `\provideverbcommand`) by default.

```
\qverb<char><verbatim material><char>
```

This macro adds quote characters around the verbatim material. Two macros are used to insert the quotes: `\qverbbeginquote` (“) and `\qverbendquote` (”). They can be redefined by the user if required. If the `csquotes` package was loaded beforehand the above macros use its macros `\openautoquote` and `\closeautoquote` to take advantage of the language dependent quotation marks. See the manual of `csquotes` for more details.

Using `\qverb<char><verbatim material><char>` is equal to `\qverbbeginquote\verb<char><verbatim material><char>\qverbendquote`, or

'`\verb<char><verbatim material><char>`' when the default definition of the quote macros is used.

`\fverb<char><verbatim material><char>`

This macro adds a frame (`\fbox{}`) around the verbatim text (`\fverb+${&^_%$+ → ${&^_}$`). A TeX box is used to store the content first, then the box is framed. The user can define similar command using the following code:

```
\newverbcommand{\myverb}{\begin{lrbox}{\verbbox}}
{\end{lrbox}\mycommand{\usebox{\verbbox}}}
```

The temporary box `\verbbox` is only provided inside a `\. . . verbcommand`.

1.3 Using `\verb` variants with short verbatim character

`\MakeSpecialShortVerb{\macro}{\char}`
`\MakeSpecialShortVerb*{\macro}{\char}`

This package also defines a special version of the `\MakeShortVerb` macro from the `shortvrb` package. The original command `\MakeShortVerb*{\char}` changes the meaning of `<char>` so that `<char><verbatim material><char>` is a shorter alternative to `\verb*<char><verbatim material><char>`.

The new macro `\MakeSpecialShortVerb*{\verb variant}{\char}` does the same, but instead of `\verb*` it uses a `\verb variant*` which needs to be defined using `\newverbcommand`. The package `shortvrb` must be installed in order to make this macro work. It is loaded automatically by `newverbs`.

The special meaning of `<char>` can be removed using `shortvrb`'s `\DeleteShortVerb`, i.e. the same way as for characters defined with the normal `\MakeShortVerb`. If a character was already made a short verbatim character it must be "deleted" before it can be redefined by `\MakeShortVerb` or `\MakeSpecialShortVerb`.

Examples:

`\MakeSpecialShortVerb{\qverb}{\"} will make ' ' a short, quoting verbatim character: "$^&$" → "$^&$".`
`\DeleteShortVerb{\"}\MakeSpecialShortVerb{\fverb}{\"} will change it definition to use \fverb: $^&$.`

`\collectverb{<code>}<char><verbatim material><char>`
`\collectverb*{<code>}<char><verbatim material><char>`
`\collectverb{<code>}{<verbatim material>}`
`\collectverb*{<code>}{<verbatim material>}`

This macro is supposed to be used with its `{<code>}` argument at the end of user or package macro which want to typeset verbatim material. It will collect everything between the following `<char>` and its next occurrence as verbatim material. An exception is if the following `<char>` is '{', then '}' is taken as the end `<char>` to simulate a normal argument to increase user friendliness. Afterwards `<code>` is expanded with `{<verbatim material>}` direct behind it. The macro ensures proper font settings to typeset the verbatim material. For this, a group is opened before the material is collected and closed directly after the given code is processed. Therefore all changes

done by the *<code>* are local and the material should be typeset directly. (In special cases when the group is disruptive, *<code>* can be a macro which reads both the verbatim material and the `\endgroup` as two arguments. However, then special care must be taken to use the correct font and some of the special characters may be active but have lost their definition.) The starred version will make spaces appear as ‘␣’ instead of displaying them as normal spaces.

```
\Collectverb{<code>}<char><verbatim material><char>
\Collectverb*{<code>}<char><verbatim material><char>
\Collectverb{<code>}{<verbatim material>}
\Collectverb*{<code>}{<verbatim material>}
```

This macro is supposed to be used with its *{<code>}* argument at the end of user or package macro which want to collect plain verbatim material suitable to be written in auxiliary files or log messages. It will collect everything between the following *<char>* and its next occurrence as verbatim material without adjusting the font or defining any characters in a special way (besides being verbatim). The starred version will make spaces appear as ‘␣’ when typeset but still be written to auxiliary files as normal spaces. An exception is if the following *<char>* is ‘{’, then ‘}’ is taken as the end *<char>* to simulate a normal argument to increase user friendliness. Afterwards *<code>* is expanded with *{<verbatim material>}* direct behind it. This macro does not add any group around the code. Should the material be typeset after all a proper font (e.g. `\ttfamily` or `\newverbsfont`) must be enabled manually.

```
\collectverbenv{<code>}
\collectverbenv*{<code>}
```

This macro is supposed to be used with its *{<code>}* argument at the end of the `\begin` of an user or package environment definition. It then collects the content of the environment as verbatim material and feeds it as an argument to the provided *<code>* like `\collectverb` does (see there for further details which also apply here). This has the following limitations: When used the `\begin` of the environment must end with a line break, i.e. the source line must not include any other material afterwards. If the environment is defined with arguments, which is supported, the line break must be after the arguments. The `\end` of the macro must be at the beginning of an own source code line. If this conditions are not met incorrect results or an error may occur. Currently trailing material on the `\begin` line is simply ignored, but this behaviour might change in future versions.

The starred version will make the spaces inside the environment appear as ‘␣’.
Example usage:

```
\newenvironment{myenv}{\maybesomeothercode\collectverbenv{\mycmd}}{\someendcode}
```

```
\Collectverbenv{<code>}
\Collectverbenv*{<code>}
```

This macro works like `\collectverbenv` but collects the environment content as plain verbatim material suitable to be written in auxiliary files or log messages. After collecting the environment the *<code>* is expanded with *{<verbatim material>}* direct behind it. This macro does not add any group around the code. Should the material be typeset after all a proper font (e.g. `\ttfamily` or `\newverbsfont`) must be enabled manually.

The starred version will make spaces appear as ‘␣’ when typeset but still be written to auxiliary files as

normal spaces.

`\newverbsfont`

Macro which activates the font used by the `newverbs` package for the verbatim text. This macro can be used manually if verbatim material collected with `\Collectverb` or `\Collectverbenv` should be typeset afterall.

```
\verbdef⟨macro⟩⟨char⟩⟨verbatim material⟩⟨char⟩
\verbdef*⟨macro⟩⟨char⟩⟨verbatim material⟩⟨char⟩
\verbdef⟨macro⟩{⟨verbatim material⟩}
\verbdef*⟨macro⟩{⟨verbatim material⟩}
```

This macro defines the `⟨macro⟩` as a robust macro which typesets the `⟨verbatim material⟩` in the usual verbatim font. For this the material is placed in a brace group with `\newverbsfont`. If a different font is wanted, this macro can be redefined locally.

If the `⟨macro⟩` existed before it will be overwritten silently. If an error should be raced instead use `\newcommand⟨macro⟩{}` just before the `\verbdef`.

Note that this macro is also provided by the `verbdef` package. If that package is loaded as well it definition of this macro is used, independent on the order of loading the two packages.

```
\Verbdef⟨macro⟩⟨char⟩⟨verbatim material⟩⟨char⟩
\Verbdef*⟨macro⟩⟨char⟩⟨verbatim material⟩⟨char⟩
\Verbdef⟨macro⟩{⟨verbatim material⟩}
\Verbdef*⟨macro⟩{⟨verbatim material⟩}
```

This macro uses `\Collectverb` internally to define `⟨macro⟩` as the plain `⟨verbatim material⟩`. This can be used to define macros for special characters, so these can be used in error or warning messages or be written into auxiliary files.

If the `⟨macro⟩` existed before it will be overwritten silently. If an error should be raced instead use `\newcommand⟨macro⟩{}` just before the `\Verbdef`.

Note that for maximum flexibility the such defined macros are not defined as robust macros. Therefore using them inside sectioning commands they should be protected using `\protect` to avoid syntax issues in the `.aux` file due to verbatim characters.

2 Compatibility with other verbatim packages

The compatibility with other verbatim packages is not tested yet. This package relies on the normal internal definition of `\verb` and `\MakeShortVerb`. Any package which changes these might break this package. Users which encounter incompatibilities should not hesitate to contact the package author (with details!).

Since v1.2 from 2011/02/16 the new verbatim macros and their short versions can be used inside `tabularx` environments. This package patches an internal macro of `tabularx` to achieve this compatibility.

3 Implementation

```
1 %<! COPYRIGHT >
2 \ProvidesPackage{newverbs}[%
3 %<! DATE >
4 %<! VERSION >
5 %< *DRIVER >
6     2099/01/01 develop
7 %</ DRIVER >
8     Define new 'verb' commands and short verb. characters]
```

3.1 Verb Definition Commands

`\newverbcommand`

`\renewverbcommand`

`\provideverbcommand`

This macro calls the real macro with the to be used definition macro.

```

9 \newcommand*\newverbcommand{\new@verbcommand\newcommand}
10 \newcommand*\renewverbcommand{\new@verbcommand\renewcommand}
11 \newcommand*\provideverbcommand{\new@verbcommand\providecommand}

```

`\new@verbcommand`

#1: underlying definition macro
 #2: macro to be defined

Checks for optional argument and calls `\new@@verbcommand` accordingly.

```

12 \def\new@verbcommand#1#2{%
13   \ifnextchar [%
14     {\new@@verbcommand{#1}{#2}}%
15     {\new@@verbcommand{#1}{#2}[\verb]}%
16 }

```

`\new@verbcommand`

#1: underlying definition macro
 #2: verb macro to be used
 #3: macro to define
 #4: code before
 #5: code after

The trailing code is inserted by patching `\verb@egroup` which is called by `\verb` after the verbatim content.

```

17 \let\newverbs@end\@empty
18 \def\new@@verbcommand#1#2[#3]#4#5{%
19   #1*#2{%
20     \bgroup
21     \newverbcommand@settings
22     \ifx\newverbs@end\@empty
23       \expandafter\def\expandafter\verb@egroup\expandafter{\%/
24         \fi
25         \begingroup\def\@tempa{#5}%
26         \expandafter\expandafter\expandafter\endgroup
27         \expandafter\expandafter\expandafter\def
28         \expandafter\expandafter\expandafter\newverbs@end
29         \expandafter\expandafter\expandafter{\expandafter\@tempa\%/
30           newverbs@end\egroup}%
31         \def\newverbs@txend{#5\egroup}%
32         \verbatim@font\let\verbatim@font\relax
33         #4#3%
34   }%

```

`\newverbs@tabularxsupport`

Enables support for the new verbatim macros inside `tabularx` environments. This environment defines its own almost-verbatim form of `\verb` which lacks the end-macro we patch above. The following code inserts such an end-macro.

```
35 \def\newverbs@tabularxsupport{%
36   \begingroup
37   \def\origa@TX@vb##1{\def\@tempa####1##1{\toks@{####1}\edef\
      @tempa{\the\toks@}%
38     \expandafter\TX@v\meaning\@tempa\\\ \ifnum0='{fi}}\
      @tempa!}
39   \def\origb@TX@vb##1{\def\@tempa####1##1{\toks@{####1}\edef\
      @tempa{\the\toks@}%
40     \expandafter\TX@v\meaning\@tempa\\\ \ifnum0='{fi}}\@tempa\
      !}%
41   \ifcase0%
42     \ifx\TX@vb\origa@TX@vb 1\else
43     \ifx\TX@vb\origb@TX@vb 1\fi\fi
44   \relax
45   \endgroup
46   \PackageWarning{newverbs}{Couldn't patch 'TX@vb' macro of
      the 'tabularx' package. Definition unknown.}%
47   \else
48   \endgroup
49   \PackageInfo{newverbs}{Patching 'TX@vb' macro of the
      'tabularx' package.}%
50   \def\TX@vb##1{\def\@tempa####1##1{\toks@{####1}\edef\
      @tempa{\the\toks@}%
51     \expandafter\TX@v\meaning\@tempa\\\ \ifnum0='{fi}}\
      newverbs@txend}\@tempa!}%
52   \fi
53   \let\newverbs@tabularxsupport\relax
54 }
```

The end-macro is initially empty and is set for every call of a new verb macro.

```
55 \def\newverbs@txend{}
      The support is activated either now or at the begin of the document if the tabularx is loaded.
56 \@ifpackageloaded{tabularx}{%
57   \newverbs@tabularxsupport
58 }{%
59   \AtBeginDocument{\@ifpackageloaded{tabularx}{\
      newverbs@tabularxsupport}{}}%
60 }
```

`\newverbcommand@settings`

Some settings required for all new `\verb`-like commands. The original end group macro from `\verb` is saved away. Also the 'temp box a' is provided with a user friendly name.

```
61 \def\newverbcommand@settings{%
62   \let\verb@orig@egroup\verb@egroup
63   \let\verbbox\@tempboxa
64 }
```

3.2 Provided New Verb Commands

`\qverb`

Quoting version of `\verb`. Places a quote character before and after the verbatim content: "verb".

```
65 \provideverbcommand{\qverb}{\qverbbeginquote}{\qverbendquote}
```

`\qverbbeginquote`

`\qverbendquote`

This macros insert the actual quotes. They can be redefined by the user to contain the required quotes. If available the quoting macros of `csquotes` are used.

```
66 \@ifundefined{openinnerquote}{%
67   \def\qverbbeginquote{‘ ’}%
68   \def\qverbendquote{’ ’}%
69 }{%
70   \def\qverbbeginquote{\openautoquote}%
71   \def\qverbendquote{\closeautoquote}%
72 }
```

`\fverb`

A framed version of `\verb`. Stores the verbatim content first into a box. Then the box content is framed.

```
73 \newverbcommand{\fverb}
74   {\setbox\verbbox\hbox\bgroup\color@setgroup}
75   {\color@endgroup\egroup\fbbox{\box\verbbox}}
```

3.3 Make Special Short Verbatim Characters

```
76 \RequirePackage{shortvrb}
```

`\MakeShortVerb`

```
77 \def\MakeShortVerb{%
78   \@ifstar
79   {\newverbs@MakeShortVerb*}%
80   {\newverbs@MakeShortVerb{}}%
81 }
```

`\newverbs@MakeShortVerb`

#1: star or empty

```
82 \def\newverbs@MakeShortVerb#1{%
83   \@ifnextchar [%
84     {\newverbs@@MakeShortVerb{#1}}%
85     {\@MakeSpecialShortVerb{#1}{\verb}}%
86 }
```

`\newverbs@MakeShortVerb`

#1: star or empty
#2: verbatim macro

```
87 \def\newverbs@MakeShortVerb#1[#2]{%  
88   \@MakeSpecialShortVerb{#1}{#2}%  
89 }
```

`\@MakeSpecialShortVerb`

#1: star or empty
#2: verbatim macro
#3: escaped short verbatim character

Uses the definition of `\MakeShortVerb` from `shortvrb` except with `\verb` replaced with the first argument. The last argument is then read by `\@MakeShortVerb`.

```
90 \def\@MakeSpecialShortVerb#1#2#3{%  
91   %\expandafter\ifx\csname cc\string#3\endcsname\relax  
92   %\else  
93   % \DeleteShortVerb{#3}%  
94   %\fi  
95   \def\@shortvrbdef{#2#1}%  
96   \@MakeShortVerb{#3}%  
97 }
```

`\MakeSpecialShortVerb`

Checks for the starred version and calls `\@MakeSpecialShortVerb` appropriately. The star needs to be added again as `\ifstar` removes it.

```
98 \newcommand*\MakeSpecialShortVerb{%  
99   \ifstar  
100   {\@MakeSpecialShortVerb{*}}%  
101   {\@MakeSpecialShortVerb{}}%  
102 }
```

3.4 Collect verbatim argument

`\collectverb`

Collects verbatim text which can be typeset. Checks for an existing star.

```
103 \newcommand*\collectverb{%  
104   \begingroup  
105   \verbatim@font  
106   \ifstar  
107     \@scollectverb  
108     \@collectverb  
109 }
```


`\@collectverb`

#1: <code>

Changes catcodes and ensures that spaces are displayed normally.

```
110 \def\@collectverb#1{%
111     \verb@eol@error
112     \let\do\@makeother
113     \dospecials
114     \@vobeyspaces
115     \frenchspacing
116     \@noligs
117     \@collectverb{#1}%
118 }
```

`\@scollectverb`

#1: <code>

Changes catcodes.

```
119 \def\@scollectverb#1{%
120     \verb@eol@error
121     \let\do\@makeother
122     \dospecials
123     \@noligs
124     \@collectverb{#1}%
125 }
```

`\@@collectverb`

#1: <code>

#2: <char>

Defines `\@@@collectverb` to read everything to the next occurrence of *<char>* and feed it to the given *<code>*.

```
126 \def\@@collectverb#1#2{%
127     \ifnum'#2='\{%
128         \catcode'\}\active
129     \else
130         \catcode'#2\active
131     \fi
132     \begingroup
133     \ifnum'#2='\{%
134         \lccode'\~'\}%
135     \else
136         \lccode'\~'#2%
137     \fi
138     \lowercase{\endgroup
139         \def\@@@collectverb#1~}{#1{##1}\endgroup}%
140     \@@@collectverb
141 }
```

`\collectverbenv`

Collects verbatim text which can be typeset. Checks for an existing star.

```

142 \newcommand*\collectverbenv{%
143     \begingroup
144     \verbatim@font
145     \@ifstar
146         \@scollectverbenv
147         \@collectverbenv
148 }

```

\@collectverbenv

#1: <code>
Changes catcodes and ensures that spaces are displayed normally.

```

149 \def\@collectverbenv#1{%
150     \newverb@catcodes
151     \@vobeyspaces
152     \frenchspacing
153     \noligs
154     \expandafter\@collectverbenv\expandafter{\@currenvir}{#1}%
155 }

```

\@scollectverbenv

#1: <code>
Changes catcodes.

```

156 \def\@scollectverbenv#1{%
157     \newverb@catcodes
158     \noligs
159     \expandafter\@collectverbenv\expandafter{\@currenvir}{#1}%
160 }

```

\@@collectverbenv

#1: <envname>
#2: <code>

```

161 \begingroup
162 \catcode'\|=0
163 \catcode'\(=1
164 \catcode'\)=2
165 \@makeother\{
166 \@makeother\}
167 \@makeother\|
168 |catcode'|^M|=active%
169 |gdef|@@collectverbenv#1#2(%
170     |long|def|@@@collectverb##1^^M##2^^M\end{#1}(|#2(|##2)|endgroup|/
171     |end(#1))%
172 |@@@collectverb%
173 |endgroup%

```

\Collectverb

Collects argument as plain verbatim and feeds it to the given code. The text is suitable to be printed to auxiliary files.

```

174 \newcommand*\Collectverb{%
175     \begingroup
176     \@ifstar
177         \@sCollectverb
178         \@Collectverb
179 }

```

\@Collectverb

#1: <code to be executed afterwards>

```

180 \def\@Collectverb#1{%
181     \verb@eol@error
182     \let\do\@makeother
183     \dospecials
184     \obeyspaces
185     \@Collectverb{#1}%
186 }

```

\@sCollectverb

#1: <code to be executed afterwards>

```

187 \def\@sCollectverb#1{%
188     \verb@eol@error
189     \let\do\@makeother
190     \dospecials
191     \@Collectverb{#1}%
192 }

```

\@@Collectverb

#1: <code to be executed afterwards>
#2: <delimiter character>

```

193 \def\@@Collectverb#1#2{%
194     \ifnum'#2='{\%
195         \catcode'\}\active
196     \else
197         \catcode'#2\active
198     \fi
199     \begingroup
200     \ifnum'#2='{\%
201         \lccode'\~'\}%
202     \else
203         \lccode'\~'#2%
204     \fi
205     \lowercase{\endgroup
206         \def\@@@Collectverb##1-}{\endgroup#1{##1}}%
207     \@@@Collectverb
208 }

```

\Collectverbenv

Collects environment content as plain verbatim and feeds it to the given code. The text is suitable to be printed to auxiliary files.

```

209 \newcommand*\Collectverbenv{%
210     \begingroup
211     \@ifstar
212     \sCollectverbenv
213     \@Collectverbenv
214 }

```

\@Collectverbenv

#1: <code to be executed afterwards>

```

215 \def\@Collectverbenv#1{%
216     \newverb@catcodes
217     \obeyspaces
218     \expandafter\@@Collectverbenv\expandafter{\@currenvir}{#1}%
219 }

```

\newverb@catcodes

```

220 \begingroup
221 \catcode'\^^I=\active
222 \gdef\newverb@catcodes{%
223     \let\do\@makeother
224     \dospecials
225     \obeylines
226     \endlinechar=13
227     \catcode'\^^I=\active
228     \def^^I{\newverb@tab}%
229 }
230 \gdef^^I{\newverb@tab}%
231 \endgroup

```

\newverb@tab

```

232 \edef\newverb@tab{\space}%\space\space\space}

```

\sCollectverbenv

#1: <code to be executed afterwards>

```

233 \def\sCollectverbenv#1{%
234     \newverb@catcodes
235     \expandafter\@@Collectverbenv\expandafter{\@currenvir}{#1}%
236 }

```

\@@Collectverbenv

```

237 \begingroup
238 \catcode'\|=0
239 \catcode'\(=1
240 \catcode'\)=2
241 \@makeother\{
242 \@makeother\}

```

```

243 \@makeother\
244 |catcode'|^M|=active%
245 |gdef|@@Collectverbenv#1#2(%
246 |long|def|@@@Collectverb##1^M##2^M\end{#1}(|endgroup#2(##2)|/
    end(#1))%
247 |@@@Collectverb%
248 )%
249 |gdef|misj(|def^M(^J))%
250 %|gdef|misj(|def^M##1(|ifx##1|endmarker|else|noexpand^M|/
    expandafter##1|fi))%
251 |endgroup%

```

\newverbsfont

```

252 \newcommand\newverbsfont{%
253   \verbatim@font
254   \frenchspacing
255 }

```

\Verbdef

```

256 \newcommand*\Verbdef{%
257   \@ifstar
258   {\@Verbdef*}%
259   {\@Verbdef{}}%
260 }

```

\@Verbdef

```

#1: <star or empty>
#2: <macro to be defined>
261 \def\@Verbdef#1#2{%
262   \Collectverb#1{\def#2}%
263 }

```

\verbdef

Provides an own definition of `\verbdef` which is also defined by the `verbdef` package.

```

264 \providecommand*\verbdef{%
265   \@ifstar
266   {\newverbs@verbdef*}%
267   {\newverbs@verbdef{}}%
268 }

```

\@Verbdef

```

#1: <star or empty>
#2: <macro to be defined>
269 \def\newverbs@verbdef#1#2{%
270   \Collectverb#1{\newverbs@@verbdef{#2}}%
271 }

```

`\@Verbdef`

`#1: <star or empty>`
`#2: <macro to be defined>`

```
272 \def\newverbs@@verbdef#1#2{%  
273   \DeclareRobustCommand{#1}{\newverbsfont#2}}%  
274 }
```